

- 1. THERMAL EXPANSION PROTECTION IS REQUIRED IN ANY DOMESTIC WATER SUPPLY SYSTEM THAT IS DOWNSTREAM FROM A BACKFLOW PREVENTION DEVICE. REFERENCE: UNIFORM PLUMBING CODE.
- 2. METER AND TRANSMITTER SUPPLIED AND INSTALLED BY TMWA.
- 3. FOR DRIVEWAY OR TRAFFIC AREAS USE 17X30 ENCLOSURE APPROVED FOR TRAFFIC RATED H/20 LOADING. SEE DETAIL 10K-18.
- 4. TOP OF METER ENCLOSURE SHALL BE SET 0.2 FEET ABOVE HIGHEST FINISHED GRADE SURROUNDING ENCLOSURE WITHIN LANDSCAPED AREAS, AND SHALL BE SET FLUSH WITH SURROUNDING FINISH GRADE IN TRAFFIC AREAS.
- 5. ENCLOSURE TO BE BACKFILLED WITH WATER PIPE BEDDING SAND ONLY, SEE SECTION 5, TRENCH BEDDING & BACKFILL.
- 6. BLANKET TO BE INSTALLED ABOVE METER AND BELOW TRANSMITTER.

MATERIAL LIST

ITEM ID	QTY.	DESCRIPTION	
MS-CHK-0.75	2.0	SETTER WATER METER, WITH ANGLE CHECK VALVE, NEW 3/4"	MIP ENDS
WSC-1.00x0.75-CTSxFIP	2.0	COUPLING SERVICE 1" CTS COMPRESSION X 3/4" FIP	
SSL-1.00	2.0	LINER RIGID STAINLESS STEEL FOR 1" CTS HDPE TUBING	
GSKT-0.75	4.0	GASKET-3/4" FOR WATER METER	
WM-DISC-0.75	2.0	3/4" WATER METER - SUPPLIED AND INSTALLED BY TMWA	
	1.0	ENCLOSURE NON-TRAFFIC 17 X 30 WATER METERS, SEE NOTE 3	
ENCL-17x30-LID-NT	1.0	COVER NON-TRAFFIC 17 X 30, NON CONCRETE FIBRELYTE LID, SEE NOTE 3	
ENCL-17x30-EXT-NT	1.0	EXTENSION BOX NON-TRAFFIC 17 X 30, SEE NOTE 3	
INSL-BLKT-4x4	1.0	BLANKET INSULATION 4' X 4' FOR WATER METERS	
RDWD-BRD-2x6x24	2.0	BOARD - REDWOOD 2" X 6" X 24"	
IDLR-0.75	2.0	IDLER WATER METER 3/4" SETTER	
ERT	2.0	REMOTE TRANSMITTER - SUPPLIED AND INSTALLED BY TMWA	
		DATE APPENDIX 10K	DRAWING N



6/2004 REV 7/2011 APPENDIX 10K
WATER METERS - SMALL
NEW RESIDENTIAL INSTALLATION
1" DUAL SERVICE
FOR 3/4" SETTERWITH ANGLE CHECK,
METER AND TRANSMITTER

DRAWING NUMBER

10K-6